



Specifications:
 Housing: LCP UL94-V0 Color: Nature
 Cove: LCP UL94-V0 Color: Black
 Contact: Phosphor Bronze
 Operating Voltage: 50V AC/DC
 Current Rating: 0.5A AC/DC
 Withstand Voltage: 250V AC/Minute
 Contact Resistance: ≤20mΩ
 Insulation resistance: ≥100MΩ
 Operating Temperature: -25℃ ~ +85℃

CKT	DIM=A	DIM=B	DIM=C	DIM=D
4P	10.5	9.3	3.0	5.1
5P	11.5	10.3	4.0	6.1
6P	12.5	11.3	5.0	7.1
7P	13.5	12.3	6.0	8.1
8P	14.5	13.3	7.0	9.1
9P	15.5	14.3	8.0	10.1
10P	16.5	15.3	9.0	11.1
11P	17.5	16.3	10.0	12.1
12P	18.5	17.3	11.0	13.1
13P	19.5	18.3	12.0	14.1
14P	20.5	19.3	13.0	15.1
15P	21.5	20.3	14.0	16.1
16P	22.5	21.3	15.0	17.1
17P	23.5	22.3	16.0	18.1
18P	24.5	23.3	17.0	19.1
19P	25.5	24.3	18.0	20.1
20P	26.5	25.3	19.0	21.1
21P	27.5	26.3	20.0	22.1
22P	28.5	27.3	21.0	23.1
23P	29.5	28.3	22.0	24.1
24P	30.5	29.3	23.0	25.1
25P	31.5	30.3	24.0	26.1
26P	32.5	31.3	25.0	27.1
27P	33.5	32.3	26.0	28.1
28P	34.5	33.3	27.0	29.1
29P	35.5	34.3	28.0	30.1
30P	36.5	35.3	29.0	31.1

一般公差
 TOLERANCES
 X. ±0.40 .XX ±0.20
 .X ±0.30 .XXX ±0.10
 ANGLES ±2°

检验尺寸标示
 SYMBOLS Ⓢ Ⓣ INDICATE
 CLASSIFICATION DIMENSION

Ⓢ MARK IS CRITICAL DIM.
 Ⓣ MARK IS MAJOR DIM.

表面处理 (FINISH)

深圳市宏利电子有限公司
 Shenzhen Holy Electronic Co.,Ltd

工程图号: FPC1012XB-nP
 品名: FPC1.0 - nP H1.2 下接
 TITLE: FPC1.0mm Pitch H=1.2 ZIF FOR SMT (BOTTON CONN)
 比例 (SCALE): 1:1
 单位 (UNITS): mm

制图 (DR): *10/03/22
 审核 (CHKD):
 核准 (APPD): Rigo Lu
 张数 (SHEET): 1 OF 1
 SIZE: A4
 REV: 0

修订 REV	修改摘要 REVISION DESCRIPTION	日期 DATE	签名 SIGNATURE